

LiO OiL P 10W-40

Description

LiO OiL P 10W-40 is a high-performance engine oil made from synthetic hydrocracked (HC) base oils of the latest engine oil generation. Its formulation reflects the latest technology, offering unrivalled properties such as:

- Prevention of sludging.
- Optimised cold start capacity.
- Fast oil distribution and supply of lube points.
- Excellent wear protection.
- Suitable for use in vehicles with catalytic converters.
- Reduced fuel consumption.

Application

LiO OiL P 10W-40 is a versatile fuel economy engine oil recommended for modern petrol and diesel engines in passenger cars. It can also be used in passenger cars and light commercial vehicles with turbocharger.

Product data

Density at 15 °C	approx. 0.865 kg/l
Viscosity at 40 °C	approx. 105 mm ² /s
Viscosity at 100 °C	> 14,60 mm ² /s
Viscosity index	> 143
COC flash point	> 199 °C
Pour point	> -39 °C

Quality rating/approvals

API CF/SL
ACEA A3/B3/B4

Performance (reliable in practice and tested in aggregates with filling instruction):

MB 229.1
VW 500.00/505.00
BMW special oil

Status 06/2011

The information in this document has been compiled with the greatest possible care and to the best of our knowledge, taking into account the latest technological development. We reserve the right to change characteristic values and application instructions without prior notice. The specified characteristic values are based on reproducible and comparable testing methods. Please always observe your duty of care as the user of our products.

