

LiO OiL P 5W-30

Description

LiO OiL P 5W-30 is a synthetic high-performance low-friction engine oil made from synthetic hydrocracked (HC) base oils of viscosity grade 5W-30. This special engine oil has the following advantages:

- Low oil consumption.
- Excellent fuel economy.
- Optimum viscosity stability.
- Excellent oxidation and temperature resistance.
- Prevents sludging and corrosion, keeping the engine clean.
- High wear protection.

Application

LiO OiL P 5W-30 is suitable for use in petrol and diesel engines with and without turbocharger of passenger cars and light commercial vehicles that require ACEA A1 or B1 products.

Product data

Density at 15 °C	approx. 0.852 kg/l
Viscosity at 40 °C	approx. 54.71 mm ² /s
Viscosity at 100 °C	> 9.7 mm ² /s
Viscosity index	> 158
COC flash point	> 199 °C
Pour point	> -36 °C

Quality rating/approvals

API SL
ACEA A1/B1

Performance (reliable in practice and tested in aggregates with filling instruction):

Ford WSS-M2C 913-B
Ford WSS-M2C 913-A
Ford WSS-M2C 912-A
Jaguar WSS-M2C913-B
Ilsac GF-3

Status 06/2011

The information in this document has been compiled with the greatest possible care and to the best of our knowledge, taking into account the latest technological development. We reserve the right to change characteristic values and application instructions without prior notice. The specified characteristic values are based on reproducible and comparable testing methods. Please always observe your duty of care as the user of our products.

