

LiO OiL Turbo 15W-40

Description

LiO OiL Turbo 15W-40 is a universal high-performance multigrade engine oil of the highest quality standard. It is suitable for all diesel and petrol engines in commercial vehicles and passenger cars (observe vehicle manufacturer instructions). It is recommended for use in urban and long-distance traffic vehicles, city busses, coaches and construction machines of all types. **LiO OiL Turbo 15W-40** also meets the specific requirements of certain vehicle transmissions. Observe the relevant manufacturer instructions.

Application

LiO OiL Turbo 15W-40 is a universal all-season oil for all naturally aspirated and turbocharged petrol and diesel engines under all operating conditions, including heavy-duty operation. It is particularly recommended for use in vehicles with prolonged oil change intervals. **LiO OiL Turbo 15W-40** is the ideal product for operators of mixed vehicles fleets.

Product data

Density at 15 °C	approx. 0.880 kg/l
Viscosity at 40 °C	approx. 97.60 mm ² /s
Viscosity at 100 °C	approx. 13.50 mm ² /s
Viscosity index	138
COC flash point	200 °C
Pour point	-24 °C

Quality rating/approvals

API CF-4/SL
ACEA E2/A3/B3/B4

Performance (reliable in practice and tested in aggregates with filling instruction):

MB 228.1/229.1
MAN M 271
Volvo VDS
VW 501.00/505.00
Caterpillar TO-2

Status 06/2011

The information in this document has been compiled with the greatest possible care and to the best of our knowledge, taking into account the latest technological development. We reserve the right to change characteristic values and application instructions without prior notice. The specified characteristic values are based on reproducible and comparable testing methods. Please always observe your duty of care as the user of our products.

